

## EARTHMAX SR 431 - Teknik Özellikler



### Description

EARTHMAX SR 431 (E-4), ağır madencilik koşullarında (yüzey ve yeraltı madenleri) çalışan güçlü taşıma kamyonları için özel olarak tasarlanmış Tamamen Çelik bir lastiktir. Yönsüz sırt deseni mükemmel çekiş ve sabitleme sağlar. Lastik, güçlü bir Tamçelik gövdeye ve kayalık, aşındırıcı ve zorlu ortamlarda bile uzun kullanım ömrünün yanı sıra olağanüstü kesilme ve kopma direnci sağlayan özel bir sırt hamuruna sahiptir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Sabit kaya kamyonu

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 25

## Dimensions International Standard

Overall Width (mm)	520
Overall Diameter (mm)	1660
Static Loaded Radius (mm)	760
Rolling Circumference (mm)	5040
Rim Rec	13.00/2.5
Star Rating	****
TRA Code	SH4
Tread Depth	49

## Load capacity (Kg)

km/h / bar

\* In case of underground mine application, consult your servicing dealer or BKT representative.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/05/2025 09:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..