

## EARTHMAX SR 43 - Teknik Özellikler



### Description

EARTHMAX SR 43 (L-4), başta yeraltı madenciliği olmak üzere zorlu kayalık koşullarda çalışan tekerlekli yükleyiciler için özel olarak tasarlanmış Tamamen Çelik bir radyal lastiktir. Lastik açık ocak maden ocakları, taş ocakları ve hurdalıklarda yük ve taşıma işlemlerinde mükemmel performans sağlar. Eşsiz sırt tasarımı üstün çekiş ve sabitleme sunar. Tamçelik gövdesi sayesinde EARTHMAX SR 43 (L-4); mükemmel dayanıklılık, takılma ve delinmelere karşı direnç ve uzun kullanım ömrü sağlar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	224 A2

## Dimensions US Standard

Usa code	94067312
Overall Width (inch)	35.4
Overall Diameter (inch)	81.7
Static Loaded Radius (inch)	37.7
Rolling Circumference (inch)	252.4
Rim Rec	28.00/3.5
Star Rating	**
TRA Code	L4

## Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	52000	55100	56800	58400	60000	61500

Printed on 4/23/2024 10:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..