

EARTHMAX SR 43 - Teknik Özellikler



Description

EARTHMAX SR 43 (L-4), başta yeraltı madenciliği olmak üzere zorlu kayalık koşullarda çalışan tekerlekli yükleyiciler için özel olarak tasarlanmış Tamamen Çelik bir radyal lastiktir. Lastik açık ocak maden ocakları, taş ocakları ve hurdalıklarda yük ve taşıma işlemlerinde mükemmel performans sağlar. Eşsiz sırt tasarımı üstün çekiş ve sabitleme sunar. Tamçelik gövdesi sayesinde EARTHMAX SR 43 (L-4); mükemmel dayanıklılık, takılma ve delinmelere karşı direnç ve uzun kullanım ömrü sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Yükleyici

Version

CUT RESISTANT COMPOUND (UMS)

Type

TL

Tyre Size

35/65 R 33

Dimensions International Standard

Overall Width (mm)	900
Overall Diameter (mm)	2076
Static Loaded Radius (mm)	957
Rolling Circumference (mm)	6412
Rim Rec	28.00/3.5
Star Rating	****
TRA Code	E4

Load capacity (Kg)

km/h / bar	-
-	-

* In case of underground mine application, consult your servicing dealer or BKT representative.

Printed on 4/20/2024 6:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..