

EARTHMAX SR 43 - Teknik Özellikler



Description

EARTHMAX SR 43 (L-4), başta yeraltı madenciliği olmak üzere zorlu kayalık koşullarda çalışan tekerlekli yükleyiciler için özel olarak tasarlanmış Tamamen Çelik bir radyal lastiktir. Lastik açık ocak maden ocakları, taş ocakları ve hurdalıklarda yük ve taşıma işlemlerinde mükemmel performans sağlar. Eşsiz sırt tasarımı üstün çekiş ve sabitleme sunar. Tamçelik gövdesi sayesinde EARTHMAX SR 43 (L-4); mükemmel dayanıklılık, takılma ve delinmelere karşı direnç ve uzun kullanım ömrü sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	228 A2

Dimensions International Standard

Overall Width (mm)	852
Overall Diameter (mm)	1877
Static Loaded Radius (mm)	844
Rolling Circumference (mm)	5702
Rim Rec	27.00/3.5
Rim Alt	27.00/3.0; 28.00/3.5
Star Rating	***
TRA Code	L4

Load capacity (Kg)

km/h / bar	6.50	6.75	7.00	7.25	7.50	7.75	8.00
10	26500	27250	28000	29000	30000	30750	31500

Printed on 4/23/2024 11:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..