

## EARTHMAX SR 44 - Teknik Özellikler



### Description

EARTHMAX SR 44 (E-4) madencilik, nakliyat ve tomrukçuluk dahil olmak üzere çeşitli uygulamalar için uygun, Tamamen Çelikten radyal bir lastiktir. E-4'ün dayanıklı diş deseni hem kusursuz çekiş hem de kullanıcı konforu sağlar. EARTHMAX SR 44 (E-4) çalıştığınız yer nerede olursa olsun, verimliliği artıracak niteliktedir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Yol ve yol dışı kamyon

Version	STANDARD
Type	TT
Tyre Size	12.00 R 20

## Dimensions International Standard

Overall Width (mm)	305
Overall Diameter (mm)	1138
Static Loaded Radius (mm)	532
Rolling Circumference (mm)	3408
Rim Rec	8.50V
Rim Alt	9.00V
Star Rating	***
TRA Code	E4

## Load capacity (Kg)

km/h / bar	7.75
50	4160

Printed on 12/2/2023 4:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..