

EARTHMAX SR 45 H2 - Teknik Özellikler



Description

EARTHMAX SR 45 H2, özel amaçlı kamyonlar için özel olarak tasarlanmış Tamamen Çelik bir radyal lastiktir. E-4 diş derinliği ve benzersiz sırt deseni, titreşimi ve sesi en aza indirerek mükemmel bir aşınma sağlar. EARTHMAX SR 45 H2, çekiş ve sabitleme gerektiren tüm operasyonlar için idealdir. Tamçelik gövde, çıkıntı ve delinmelere karşı mükemmel direnç ve uzun bir servis ömrü sağlar. Standart, ısıya dirençli ve kesilmeye dirençli hamurdan yapılmış versiyon mevcuttur.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	212 B

Dimensions US Standard

Usa code	94063802
TMPH	228
Overall Width (inch)	26
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	38.5
Rolling Circumference (inch)	259.7
Rim Rec	17.00/3.5
Rim Alt	---
Star Rating	***
TRA Code	E4

Load capacity (lbs)

mph / psi	105	109	112	116
30	41900	42500	43000	44100

Printed on 4/17/2024 5:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..