

EARTHMAX SR 45 PLUS - Teknik Özellikler



Description

EARTHMAX SR 45 PLUS özellikle sabit damperli kamyonlar için tasarlanmış Tamamen Çelikten radyal bir lastiktir. Uzun mesafelerdeki çalışmalar için idealdir. EARTHMAX SR 45 PLUS'ın dış deseni titreşim ve gürültüyü en aza indirir.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

Version	STANDARD COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions US Standard

Usa code	94049806
TMPH	370
Overall Width (inch)	29.4
Overall Diameter (inch)	106.4
Static Loaded Radius (inch)	47.8
Rolling Circumference (inch)	318.7
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Printed on 6/8/2023 3:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..