

EARTHMAX SR 454 - Veri Sayfasını İndir



Description

EARTHMAX SR 454, güçlü taşıma kamyonları için özel olarak tasarlanmış Tam Çelik bir radyal lastiktir. Benzersiz E-3 sırt tasarımı ve özel merkez kanalı, hem yumuşak hem çamurlu yüzeylerde gelişmiş yanıl çekiş ve elleçleme sağlar. Bu lastik özellikle daha serin çalışma sıcaklığında daha yüksek hızlar, uzun mesafeler için tasarlanmıştır. Çok katmanlı çelik kuşaklara sahip Tamamen Çelik yapı, sonuç olarak daha yüksek üretkenlik için çalışma süresini artırmak üzere şok ve kaya delinmelerine karşı üstün koruma sağlar. EARTHMAX SR 454'ün kare omzu, titreşim ve gürültüyü en aza indirmenin yanı sıra mükemmel manevra kabiliyeti ve sabitleme için zemin temasını en üst düzeye çıkarır.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	525
27.00 R 49	HEAT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	725
27.00 R 49	STANDARD COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	640

Printed on 12/4/2023 5:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..