EARTHMAX SR 468 - Teknik Özellikler

Description

EARTHMAX SR 468, güçlü taşıma kamyonları için özel olarak tasarlanmış Tam Çelik bir radyal lastiktir. Özel sırt hamuru ile benzersiz sırt tasarımı onu sert, kayalık ve zorlu madencilik koşulları için mükemmel kılıyor. Çevresel kanallara sahip sırt diş blokları ve iç içe geçen bloklar etkili ısı yayılımı sağlar. Ayrıca sağlam kare omuz, lastiği hasardan korumak için gevşek taşları çıkarmaya yardımcı olur. EARTHMAX SR 468, ağır yükleri taşımak, daha uzun kullanma süresi sağlamak ve kaya kesilmelerine ve delinmelere karşı direnç sağlamak için BKT'nin en son teknolojisi kullanılarak geliştirilmiştir.

UM

International Standard

Construction

RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	50/80 R 57
LI/SS	257 B

Dimensions International Standard

TKPH	1340
Overall Width (mm)	1205
Overall Diameter (mm)	3610
Static Loaded Radius (mm)	1597
Rolling Circumference (mm)	10870
Rim Rec	32.00/6.0
Rim Alt	29.00/6.0
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	61500	63000	65000	67000	69000	71000	73000

Printed on 4/29/2024 1:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..