

EARTHMAX SR 468 - Veri Sayfasını İndir



Description

EARTHMAX SR 468, güçlü taşıma kamyonları için özel olarak tasarlanmış Tam Çelik bir radyal lastiktir. Özel sırt hamuru ile benzersiz sırt tasarımı onu sert, kayalık ve zorlu madencilik koşulları için mükemmel kılıyor. Çevresel kanallara sahip sırt dış blokları ve iç içe geçen bloklar etkili ısı yayılımı sağlar. Ayrıca sağlam kare omuz, lastiği hasardan korumak için gevşek taşları çıkarmaya yardımcı olur. EARTHMAX SR 468, ağır yükleri taşımak, daha uzun kullanma süresi sağlamak ve kaya kesilmelerine ve delinmelere karşı direnç sağlamak için BKT'nin en son teknolojisi kullanılarak geliştirilmiştir.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
37.00 R 57	CUT RESISTANT COMPOUND	94069354	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	497
37.00 R 57	HEAT RESISTANT COMPOUND	94069347	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	699
37.00 R 57	STANDARD COMPOUND	94069361	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	582
40.00 R 57	CUT RESISTANT COMPOUND	94068845	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	548
40.00 R 57	HEAT RESISTANT COMPOUND	94067381	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	774
40.00 R 57	STANDARD COMPOUND	94068852	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	651
46/90 R 57	CUT RESISTANT COMPOUND	94070589	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	565
46/90 R 57	HEAT RESISTANT COMPOUND	94070596	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	798
46/90 R 57	STANDARD COMPOUND	94070602	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	671
50/80 R 57	CUT RESISTANT COMPOUND	94075164	E4	**	257 B	32.00/6.0	34.00/6.0 , 29.00/6.0	47.4	142.1	62.9	428	TL	651
50/80 R 57	HEAT RESISTANT COMPOUND	94075157	E4	**	257 B	32.00/6.0	34.00/6.0 , 29.00/6.0	47.4	142.1	62.9	428	TL	918
50/80 R 57	STANDARD COMPOUND	94074228	E4	**	257 B	32.00/6.0	34.00/6.0 , 29.00/6.0	47.4	142.1	62.9	428	TL	774

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/14/2024 11:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..