

EARTHMAX SR 46 - Teknik Özellikler



Description

Earthmax SR 46, sabit damperli kamyonlar için BKT'nin çok engebeli, aşındırıcı ve zorlu madencilik sahalarına verdiği yenilikçi yanıttır. Lastik, kesilmelere ve parçalanmalara karşı üstün dayanıklılık ve uzun lastik ömrü sunarken, ağır yükler taşımak için özel olarak tasarlanmıştır. Tamamen Çelik gövde ve kuşaklar çalışma süresini maksimuma çıkarmak ve verimliliği geliştirmek üzere darbelere, aksam yorulmasına ve sönmeye karşı olağanüstü koruma sağlar. Earthmax SR 46 en az dış yüzü hasarı ile viraj alma performansını iyileştirmek için çevresel oluklu, özel çekme blok desenine sahiptir.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 33.00 R 51 |
| LI/SS | 235 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94061723 |
| TMPH | 382 |
| Overall Width (inch) | 35.6 |
| Overall Diameter (inch) | 120.1 |
| Static Loaded Radius (inch) | 55.2 |
| Rolling Circumference (inch) | 369.2 |
| Rim Rec | 24.00/5.0 |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (lbs)

| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 66000 | 68000 | 71500 | 74000 | 76000 | 78500 | 80500 | 82500 | 85500 |

Printed on 4/13/2024 8:12 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..