



# EARTHMAX SR 47 TP - Teknik Özellikler

## Description

EARTHMAX SR 47 TP (E-4), maksimum çekiş ve delinme direnci gerektiren koşullarda çalışan güçlü taşıma kamyonları için özel olarak tasarlanmış Tamamen Çelik bir radyal lastiktir. E-4 diş derinliği, uzun mesafelerde bile uzun süreli aşınma ömrü sağlayarak çalışma kesintisi süresini azaltır ve üretkenliği artırır. EARTHMAX SR 47 TP, özellikle çamurlu ve kaygan arazilerde hem çekiş hem de stabilite gerektiren her türlü görev için mükemmeldir. Standart ve kesilmeye dirençli hamurdan yapılmış versiyonlar mevcuttur.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Yoldışı: Sabit kaya kamyonu

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

## Dimensions US Standard

Usa code	94074204
TMPH	258
Overall Width (inch)	25.6
Overall Diameter (inch)	86
Static Loaded Radius (inch)	38.8
Rolling Circumference (inch)	260.8
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 5/5/2024 10:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..