



EARTHMAX SR 47 TP - Teknik Özellikler

Description

EARTHMAX SR 47 TP (E-4), maksimum çekiş ve delinme direnci gerektiren koşullarda çalışan güçlü taşıma kamyonları için özel olarak tasarlanmış Tamamen Çelik bir radyal lastiktir. E-4 diş derinliği, uzun mesafelerde bile uzun süreli aşınma ömrü sağlayarak çalışma kesintisi süresini azaltır ve üretkenliği artırır. EARTHMAX SR 47 TP, özellikle çamurlu ve kaygan arazilerde hem çekiş hem de stabilite gerektiren her türlü görev için mükemmeldir. Standart ve kesilmeye dirençli hamurdan yapılmış versiyonlar mevcuttur.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

Version	STANDARD COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions International Standard

TKPH	440
Overall Width (mm)	650
Overall Diameter (mm)	2185
Static Loaded Radius (mm)	985
Rolling Circumference (mm)	6625
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Printed on 5/5/2024 10:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..