

EARTHMAX SR 475 - Teknik Özellikler



Description

EARTHMAX SR 475, Güçlü Damperli Kamyonlar için tasarlanmış, tamçelik bir radyal lastiktir. Özellikle uzun mesafeli, zorlu ve kayalıklı ortamlardaki işlemler için idealdir. Benzersiz sırt tasarımı, sıcak iklimde daha düşük bir ısı üretir ve mükemmel çekiş sağlar. Güçlü tamçelik gövdesi ve kuşakları, mükemmel denge ve çıkıntı ve delinmelere karşı direnç sağlar. EARTHMAX SR 475, olağanüstü manevra kabiliyeti ve kullanım sağlayarak zeminle teması en üst düzeye çıkaran kare omuzlar ile tasarlanmıştır.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

| | |
|-----------|-------------------|
| Version | STANDARD COMPOUND |
| Type | TL |
| Tyre Size | 18.00 R 33 |
| LI/SS | 195 B |

Dimensions International Standard

| | |
|----------------------------|-----------|
| TKPH | 292 |
| Overall Width (mm) | 490 |
| Overall Diameter (mm) | 1860 |
| Static Loaded Radius (mm) | 860 |
| Rolling Circumference (mm) | 5721 |
| Rim Rec | 13.00/2.5 |
| Star Rating | *** |
| TRA Code | E4 |

Load capacity (Kg)

| km/h / bar | 7.25 | 7.50 | 7.75 | 8.00 |
|------------|-------|-------|-------|-------|
| 50 | 11200 | 11500 | 11800 | 12150 |

Printed on 4/27/2024 10:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..