

## EARTHMAX SR 475 - Veri Sayfasını İndir



### Description

EARTHMAX SR 475, Güçlü Damperli Kamyonlar için tasarlanmış, tamçelik bir radyal lastiktir. Özellikle uzun mesafeli, zorlu ve kayalıklı ortamlardaki işlemler için idealdir. Benzersiz sırt tasarımı, sıcak iklimde daha düşük bir ısı üretir ve mükemmel çekiş sağlar. Güçlü tamçelik gövdesi ve kuşakları, mükemmel denge ve çıkıntı ve delinmelere karşı direnç sağlar. EARTHMAX SR 475, olağanüstü manevra kabiliyeti ve kullanım sağlayarak zeminle teması en üst düzeye çıkaran kare omuzlar ile tasarlanmıştır.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Sabit kaya kamyonu

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
<b>18.00 R 33</b>	CUT RESISTANT COMPOUND	E4	**	191 B	13.00/2.5		490	1860	860	5721	TL	265
<b>18.00 R 33</b>	CUT RESISTANT COMPOUND	E4	***	195 B	13.00/2.5		490	1860	860	5721	TL	265
<b>18.00 R 33</b>	STANDARD COMPOUND	E4	***	195 B	13.00/2.5		490	1860	860	5721	TL	292
<b>24.00 R 35</b>	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5		654	2160	971	6589	TL	355
<b>24.00 R 35</b>	STANDARD COMPOUND	E4	**	209 B	17.00/3.5		654	2160	971	6589	TL	422

Printed on 12/9/2023 9:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..