# EARTHMAX SR 47 - Teknik Özellikler

## Description

EARTHMAX SR 47 (E-4), taş kesiklerine ve delinmelere karşı maksimum dayanıklılık gerektiren koşullarda çalışan, sabit damperli kamyonlar için özel olarak tasarlanmış, Tamamen Çelikten radyal bir lastiktir. E-4'ün diş derinliği ve eşsiz diş tasarımı uzun mesafelerde bile uzun sürede aşınma sağlar ve bu sayede çalışmama sürelerini azaltır, verimliliği artırır. Standart ve kesilmeye karşı dayanıklı bileşenler ile sunulmaktadır.

## UM

US Standard

## Construction

RADIAL

## Machinery

Yoldışı: Sabit kaya kamyonu

| | |
|---|---|
| **Version** | CUT RESISTANT COMPOUND |
| **Type** | TL |
| **Tyre Size** | 24.00 R 35 |
| **LI/SS** | 212 B |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94060917 |
| **TMPH** | 182 |
| **Overall Width (inch)** | 26.4 |
| **Overall Diameter (inch)** | 85.9 |
| **Static Loaded Radius (inch)** | 38.7 |
| **Rolling Circumference (inch)** | 258.5 |
| **Rim Rec** | 17.00/3.5 |
| **Rim Alt** | -- |
| **Star Rating** | *** |
| **TRA Code** | E4 |

## Load capacity (lbs)

| mph / psi | 105 | 109 | 112 | 116 |
|---|---|---|---|---|
| **30** | 41900 | 42500 | 43000 | 44100 |

Printed on 7/27/2024 11:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..