

## EARTHMAX SR 48 - Teknik Özellikler



### Description

EARTHMAX SR 48 Tamamen Çelikten yapılmış radyal lastik güçlü taşıma kamyonları için özel olarak tasarlanmış ve üretilmiştir. Kayalıklı ortamlardaki en zorlu çalışma koşullarında bile geliştirilmiş çekiş ve sıra dışı sırt direnci sağlar. Bu lastik ağır yüklerle çalışmak için idealdir. Kare omuz tasarımı, yanağı kesilmelere ve hasara karşı korur. EARTHMAX SR 48'in güçlü Tamçelik gövdesi şoklara ve kayalar tarafından delinmeye karşı olağanüstü koruma sağlayarak üretkenliği artırır.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Sabit kaya kamyonu

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

## Dimensions US Standard

Usa code	94060276
TMPH	212
Overall Width (inch)	26.2
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	39.1
Rolling Circumference (inch)	260.7
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 4/25/2024 6:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..