

EARTHMAX SR 48 - Teknik Özellikler



Description

EARTHMAX SR 48 Tamamen Çelikten yapılmış radyal lastik güçlü taşıma kamyonları için özel olarak tasarlanmış ve üretilmiştir. Kayalıklı ortamlardaki en zorlu çalışma koşullarında bile geliştirilmiş çekiş ve sıra dışı sırt direnci sağlar. Bu lastik ağır yüklerle çalışmak için idealdir. Kare omuz tasarımı, yanağı kesilmelere ve hasara karşı korur. EARTHMAX SR 48'in güçlü Tamçelik gövdesi şoklara ve kayalar tarafından delinmeye karşı olağanüstü koruma sağlayarak üretkenliği artırır.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

| | |
|-----------|-------------------|
| Version | STANDARD COMPOUND |
| Type | TL |
| Tyre Size | 27.00 R 49 |
| LI/SS | 223 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94055142 |
| TMPH | 349 |
| Overall Width (inch) | 29.1 |
| Overall Diameter (inch) | 105.8 |
| Static Loaded Radius (inch) | 48.2 |
| Rolling Circumference (inch) | 321.5 |
| Rim Rec | 19.50/4.0 |
| Rim Alt | -- |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (lbs)

| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 45400 | 48100 | 49400 | 50700 | 52000 | 55100 | 56800 | 58400 | 60000 |

Printed on 4/25/2024 9:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..