

EARTHMAX SR 49 - Teknik Özellikler



Description

EARTHMAX SR 49, yükleyiciler ve dozerler, düşük profilli damperli kamyonlar (LPDT) ve yük taşıma damperleri (LHD) için tasarlanmış Tamamen Çelik bir radyal lastiktir. EARTHMAX SR 49, olağanüstü çekiş ve sabitleme gerektiren zorlu madencilik operasyonlarında optimum performans sağlar. Lastik yönlü bir desene sahiptir ve mükemmel dayanıklılık sağlayan kesilmeye karşı dirençli özel bir hamurdan yapılmıştır.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Dozer • Yük taşıma damperi (LHD) • Yükleyici • Düşük profilli damperli kamyon

Version

CUT RESISTANT COMPOUND

Type

TL

Tyre Size

35/65 R 33

Dimensions US Standard

Usa code	94051939
Overall Width (inch)	35.4
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	35
Rolling Circumference (inch)	241.1
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	****
TRA Code	E4

Load capacity (lbs)

mph / psi

* "consult your servicing dealer or BKT representative for speed, load and pressure details."

Printed on 3/4/2024 10:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..