

## EARTHMAX SR 50 - Teknik Özellikler



### Description

EARTHMAX SR 50 (L-5), yükleyiciler için özel olarak tasarlanmış, Tamamen Çelikten radyal bir lastiktir. Dayanıklı gövde ve yanak koruyucuları, en zorlu operasyonlar için idealdir. EARTHMAX SR 50, aşınma süresini uzatan, kesilmeye karşı dayanıklı özel bileşikten üretilmiştir. Araç kullanıcıları ayrıca kusursuz çekiş, istikrar ve konforlu sürüş özelliklerinden memnun kalırlar.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	209 A2

## Dimensions International Standard

Overall Width (mm)	690
Overall Diameter (mm)	1772
Static Loaded Radius (mm)	806
Rolling Circumference (mm)	5334
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	L5

## Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	15500	16000	16500	17000	18000	18500

Printed on 4/20/2024 6:09 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..