



## EARTHMAX SR 50 - Veri Sayfasını İndir

### Description

EARTHMAX SR 50 (L-5), yükleyiciler için özel olarak tasarlanmış, Tamamen Çelikten radyal bir lastiktir. Dayanıklı gövde ve yanak koruyucuları, en zorlu operasyonlar için idealdir. EARTHMAX SR 50, aşınma süresini uzatan, kesilmeye karşı dayanıklı özel bileşikten üretilmiştir. Araç kullanıcıları ayrıca kusursuz çekiş, istikrar ve konforlu sürüş özelliklerinden memnun kalırlar.



### UM

International Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Yükleyici

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 R 25	CUT RESISTANT COMPOUND	L5	*	202 A2	22.00/3.0		690	1772	806	5334	TL
26.5 R 25	CUT RESISTANT COMPOUND	L5	**	209 A2	22.00/3.0		690	1772	806	5334	TL
29.5 R 25	CUT RESISTANT COMPOUND	L5	*	208 A2	25.00/3.5		775	1901	862	5722	TL
29.5 R 25	CUT RESISTANT COMPOUND	L5	**	216 A2	25.00/3.5		775	1901	862	5722	TL

Printed on 4/20/2024 12:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..