

EARTHMAX SR 51 - Teknik Özellikler



Description

EARTHMAX SR 51 (L-5), yükleyiciler ve dozerler için özel olarak tasarlanmış, Tamamen Çelikten radyal bir lastiktir. EARTHMAX SR 51 kesilmelere karşı daha fazla dayanıklılık, yanak koruması ve olağanüstü çekiş gerektiren zorlu operasyonlar için idealdir.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Dozer • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	224 A2

Dimensions International Standard

Overall Width (mm)	905
Overall Diameter (mm)	2061
Static Loaded Radius (mm)	872
Rolling Circumference (mm)	6082
Rim Rec	28.00/3.5
Star Rating	**
TRA Code	L5

Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	23600	25000	25750	26500	27250	28000

Printed on 2/21/2024 6:09 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..