

EARTHMAX SR 51 - Teknik Özellikler



Description

EARTHMAX SR 51 (L-5), yükleyiciler ve dozerler için özel olarak tasarlanmış, Tamamen Çelikten radyal bir lastiktir. EARTHMAX SR 51 kesilmelere karşı daha fazla dayanıklılık, yanak koruması ve olağanüstü çekiş gerektiren zorlu operasyonlar için idealdir.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Dozer • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	221 A2

Dimensions International Standard

Overall Width (mm)	878
Overall Diameter (mm)	1872
Static Loaded Radius (mm)	814
Rolling Circumference (mm)	5616
Rim Rec	27.00/3.5
Rim Alt	27.00/3.0; 28.00/3.5
Star Rating	**
TRA Code	L5

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25
10	21800	23000	23600	24300	25000	25750

Printed on 4/26/2024 12:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..