

EARTHMAX SR 53 - Teknik Özellikler



Description

EARTHMAX SR 53, yeraltı operasyonları ve hurdalıklar da dahil olmak üzere zorlu kayalık koşullarında çalışan yükleyiciler veya dozerler, düşük profilli damperli kamyonlar (LPDT) ve yük taşıma damperleri (LHD) için özel olarak tasarlanmış Tamamen Çelik bir radyal lastiktir. Derin L-5 sırt ve kesilmeye karşı dirençli hamur, mükemmel çekiş ve sabitlemeye ek olarak daha uzun bir kullanım ömrü sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Dozer • Yükleyici • Düşük profilli damperli kamyon

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	29.5 R 25

Dimensions International Standard

Overall Width (mm)	770
Overall Diameter (mm)	1912
Static Loaded Radius (mm)	859
Rolling Circumference (mm)	5755
Rim Rec	25.00/3.5
Star Rating	**
TRA Code	L5

Load capacity (Kg)

* "consult your servicing dealer or BKT representative for load and pressure details."

Printed on 4/19/2024 3:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..