

EARTHMAX SR 55 - Teknik Özellikler



Description

EARTHMAX SR 55, en ağır taş ocağı ve madencilik operasyonlarında ve hurdalıklarda çalışan yükleyiciler, dozerler ve yük taşıma damperleri için özel olarak tasarlanmış Tamamen Çelik bir radyal lastiktir. Ekstra derin ve pürüzsüz sırt tasarımının sağladığı mükemmel kesilme koruması sayesinde EARTHMAX SR 55, müthiş dayanıklılık ve daha az çalışmama süresi ile en yüksek düzey üretkenliğe ulaşabilir. Ayrıca ekipman operatörleri, olağanüstü sabitleme ve çekişten memnun kalacaklardır.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Dozer • Yük taşıma damperli (LHD) • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	193 A2

Dimensions International Standard

Overall Width (mm)	535
Overall Diameter (mm)	1543
Static Loaded Radius (mm)	700
Rolling Circumference (mm)	4644
Rim Rec	17.00/2.0
Star Rating	**
TRA Code	L5S

Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	9750	10000	10300	10900	11200	11500

Printed on 4/27/2024 11:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..