

EARTHMAX SR 57 - Teknik Özellikler



Description

EARTHMAX SR 57, yeraltı madenlerinde çalışan yükleyiciler, dozerler ve hizmet araçları için özel olarak tasarlanmış Tamamen Çelik radyal lastiktir. Lastik, zorlu ve kayalık yüzeylerde üstün çekiş, sabitleme ve konfor sağlar. L-5 ekstra derin sırt ve özel olarak formüle edilmiş UMS (yeraltı madeni hizmeti) hamuru, kaya kesiklerine ve delinmelere karşı olağanüstü dirence ek olarak daha uzun bir lastik aşınma ömrü sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Dozer • Yük taşıma damperi (LHD) • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TT
Tyre Size	10.00 R 20

Dimensions US Standard

Usa code	94073290
Overall Width (inch)	10.7
Overall Diameter (inch)	43.5
Rim Rec	7.5
Star Rating	*
TRA Code	L5

Load capacity (lbs)

mph / psi	102
3.7	9610

Printed on 4/25/2024 8:09 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..