

## EARTHMAX SR 57 - Teknik Özellikler



### Description

EARTHMAX SR 57, yeraltı madenlerinde çalışan yükleyiciler, dozerler ve hizmet araçları için özel olarak tasarlanmış Tamamen Çelik radyal lastiktir. Lastik, zorlu ve kayalık yüzeylerde üstün çekiş, sabitleme ve konfor sağlar. L-5 ekstra derin sırt ve özel olarak formüle edilmiş UMS (yeraltı madeni hizmeti) hamuru, kaya kesiklerine ve delinmelere karşı olağanüstü dirence ek olarak daha uzun bir lastik aşınma ömrü sağlar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Dozer • Yük taşıma damperi (LHD) • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TT
Tyre Size	7.50 R 15

## Dimensions US Standard

Usa code	94051687
Overall Width (inch)	8.8
Overall Diameter (inch)	33.3
Rim Rec	6.00
Rim Alt	6.5
Star Rating	*
TRA Code	L5

## Load capacity (lbs)

mph / psi	102
3.7	5730

Printed on 4/25/2024 10:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..