

EARTHMAX SR LOADER - Teknik Özellikler



Description

EARTHMAX SR LASTİKLİ YÜKLEYİCİ, yükleme ve kürüme işlemlerinin yanı sıra Belden kırmalı kaya kamyonu uygulamaları için tasarlanmış bir yol dışı lastiktir. Tam Çelik gövdesinin yanı sıra çok katmanlı çelik kuşakları ve benzersiz sırt hamuru, çıkıntı ve delinmelere karşı mükemmel direnç sağlayarak daha uzun bir kullanma süresi sunar. EARTHMAX SR LOADER, üstün kendi kendini temizleme özellikleri ve çeşitli arazi tiplerinde mükemmel çekiş gücü sağlayan benzersiz bir sırt desenine sahiptir.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Dozer • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B/202 A2

Dimensions International Standard

TKPH	230
Overall Width (mm)	681
Overall Diameter (mm)	1735
Static Loaded Radius (mm)	763
Rolling Circumference (mm)	5179
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E3/L3
Tread Depth	34

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	9500	9750	10300	10600	11200	11500
10	12850	13200	14000	14500	15000	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/10/2025 12:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..