

EM 934 - Teknik Özellikler



Description

EM 934 yol inşaatı uygulamalarında kullanılan ekskavatörler için özel olarak tasarlanmıştır. Sıra dışı kendini temizleme özelliklerinin yanı sıra, kusursuz yanıl çekiş özelliğine sahiptir. Güçlü gövdesi uzun bir hizmet ömrü sunarken, eşsiz diş bileşiği kesilme ve parçalanmalara karşı dayanıklılık sağlar.

UM

International Standard

Construction

❖ BIAS

Machinery

Endüstriyel: Ekskavatör

Version	SPECIAL
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	280
Overall Diameter (mm)	1060
Static Loaded Radius (mm)	500
Rolling Circumference (mm)	3208
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (Kg)

km/h / bar	7.50
50	3000

Printed on 4/25/2024 5:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..