

EM 936 LOADER SPECIAL - Teknik Özellikler



Description

EM 936 LOADER SPECIAL yükleme uygulamalarında kullanılan teleskopik taşıyıcılar için özel olarak tasarlanmıştır. Olağanüstü sürüş konforu ve gelişmiş kendini temizleme özelliklerine sahiptir. Ayrıca yüksek seviyede yol tutuşu ve ağır yük gerektiren koşullarda bile kusursuz çekiş gücü sağlar.

UM

US Standard

Construction

 BIAS

Machinery

Endüstriyel: Yükleyici • Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20 (405/70 - 20)
LI/SS	149 B

Dimensions US Standard

Usa code	94028771
Ply Rating	14
Overall Width (inch)	15.9
Overall Diameter (inch)	42.9
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	129.7
Rim Rec	13 SDC
Rim Alt	13
TRA Code	E2

Load capacity (lbs)

mph / psi	51
30	7150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/14/2025 6:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..