

EM 936 SUPER - Teknik Özellikler



Description

EM 936 SUPER kazma ve yükleme operasyonlarında ve taşımacılık uygulamalarında kullanılmak üzere özellikle ekskavatörler ve teleskopik yükleyiciler için tasarlanmıştır. %8-10 oranında artırılmış sırt genişliğiyle EM 936 SUPER üstün sabitleme ve geliştirilmiş sürüş konforu sunar. Ayrıca ağır hizmet koşullarında bile yüksek seviyede elleçleme konforu ve mükemmel çekiş sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Ekskavatör

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

Dimensions International Standard

Ply Rating	16
Section Width (mm)	277
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	500
Rolling Circumference (mm)	3336
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (Kg)

km/h / bar	7.50
50	3000

Printed on 4/27/2024 6:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..