

EM 936 - Teknik Özellikler



Description

EM 936 kazı ve yükleme çalışmalarında kullanılan ekskavatörler ve teleskopik taşıyıcılar için özel olarak tasarlanmıştır. Bunun yanında, lastiğin bir boyutu özellikle toprak düzeltme, yükleme ve taşıma uygulamalarında kullanılan greyderler ve yükleyiciler için uygundur. EM 936 olağanüstü sürüş konforu ve gelişmiş kendini temizleme özelliklerine sahiptir. Ayrıca yüksek seviyede yol tutuşu ve ağır yük gerektiren koşullarda bile kusursuz çekiş gücü sağlar. "Özel" modeli, özel bileşikten üretilmiştir.

UM

US Standard

Construction

❖ BIAS

Machinery

Endüstriyel: Ekskavatör • Teleskopik yükleyici

Version	DUAL BEAD
Type	TL
Tyre Size	17.5 - 25

Dimensions US Standard

Usa code	94066643
Ply Rating	24
Overall Width (inch)	17.7
Overall Diameter (inch)	52.8
Static Loaded Radius (inch)	23.6
Rolling Circumference (inch)	159.8
Rim Rec	14.00/1.5
TRA Code	E2/L2

Load capacity (lbs)

mph / psi	102
5	22045

Printed on 12/11/2023 2:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..