

EM 937 (E3) - Teknik Özellikler



Description

EM 937 (E-3) açık işletme madenciliği uygulamalarında kullanılan sabit damperli kamyonlar için özel olarak tasarlanmıştır. Kusursuz sağlamlığa ve kesilme ve parçalanmalara karşı yüksek dayanıklılığa sahiptir. EM 937 (E-3) özellikle ağır yük gerektiren işler için uygundur.

UM

International Standard

Construction

 BIAS

Machinery

Yoldışı: Sabit kaya kamyonu

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4105
Rim Rec	10.00/1.5
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	6.50	9.25
50	5600	-
10	-	10000

Printed on 12/5/2023 11:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..