



EM 937 (E3) - Veri Sayfasını İndir



Description

EM 937 (E-3) açık işletme madenciliği uygulamalarında kullanılan sabit damperli kamyonlar için özel olarak tasarlanmıştır. Kusursuz sağlamlığa ve kesilme ve parçalanmalara karşı yüksek dayanıklılığa sahiptir. EM 937 (E-3) özellikle ağır yük gerektiren işler için uygundur.

UM

International Standard

Construction

 BIAS

Machinery

Yoldışı: Sabit kaya kamyonu

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
14.00 - 25	STANDARD	E3/L3	28	10.00/1.5		375	1368	620	4105	TT	26
14.00 - 25	STANDARD	E3/L3	28	10.00/1.5		375	1368	620	4105	TL	26

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/11/2025 11:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..