

EM 937 IND3 (ECH) - Teknik Özellikler



Description

EM 937 (E-3) IND istifleme ve yükleme çalışmalarında kullanılan boş konteyner istifleme araçları için özel olarak tasarlanmıştır. Kusursuz dayanıklılığa ve uzun lastik ömrüne sahiptir. EM 937 (E-3) IND asfalt yüzeyler ve limanda yükleme-boşaltma gerektiren bütün operasyonlar için idealdir. *For size 14.00-24 please confirm service rim or consult manufacturer/distributor

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Bş konteyner taşıyıcısı

Version	PORT INDUSTRIAL
Type	TT
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	628
Rolling Circumference (mm)	4050
Rim Rec	10.00 W
TRA Code	IND3

Load capacity (Kg)

km/h / bar	10.00
10	13500

Printed on 4/20/2024 3:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..