

## EM 938 - Teknik Özellikler



### Description

EM 938 yol inşaatı işlerinde kullanılan ekskavatörler için özel olarak tasarlanmıştır. Lastik kesilme ve yarılmalara karşı özellikle dayanıklı olan özel diş bileşiminden üretilmiştir, güçlü diş deseni ise kusursuz çekiş gücü sağlar. EM 938 sıra dışı kendini temizleme özelliklerine sahiptir. Güçlü gövde, ağır yük gerektiren işlerde bile darbelere ve sarsılmalara karşı olağanüstü dayanıklılık sağlar.

### UM

US Standard

### Construction

BIAS

### Machinery

Endüstriyel: Ekskavatör

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20
LI/SS	140 B

## Dimensions US Standard

Usa code	94046034
Ply Rating	14
Overall Width (inch)	10.1
Overall Diameter (inch)	39.8
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	120.9
Rim Rec	7.0
Rim Alt	6.5 ; 7.5
TRA Code	E2

## Load capacity (lbs)

mph / psi	102
30	5510

Printed on 12/5/2023 11:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..