

F 240 - Teknik Özellikler



Description

F 240 tomrukçuluk uygulamaları için tasarlanmış, ormancılığa yönelik bir lastiktir. Diş deseni sağlıklı yönlendirmeye ek olarak kusursuz çekiş ve kendini temizleme özellikleri de sunar. Üstün diş bileşiği kesilme ve aşınmaya karşı olağanüstü dayanıklılık ve bunun sonucunda daha uzun hizmet ömrü sağlar. F 240 daha fazla istikrar için daha geniş temas alanına sahiptir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Tomruk yükleme

Version	STANDARD
Type	TT
Tyre Size	400 - 15.5 (400 - 15.5)

Dimensions International Standard

Ply Rating	12
Section Width (mm)	405
Overall Diameter (mm)	865
Rim Rec	AG 13.00
ECE	E11-106R-004260
TRA Code	LS2

Load capacity (Kg)

km/h / bar	3.80
30	3150

Printed on 4/26/2024 6:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..