

## FARM 2000 PLUS - Teknik Özellikler



### Description

FARM 2000 PLUS, tarlalarda daha iyi performans için daha fazla diş içeren bir tarım lastiğidir. Derin sırt daha uzun lastik ömrü ve mükemmel çekiş sağlarken, üstün sırt hamuru daha iyi kesilme ve kopma direnci sağlar. FARM 2000 PLUS, mükemmel kendi kendini temizleme özellikleri sergiler ve özel olarak tasarlanmış diş açları lastiği özellikle arazi ve taşıma uygulamaları için uygun kılar.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: Traktör

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	143 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	440
Overall Diameter (mm)	1435
Static Loaded Radius (mm)	657
Rolling Circumference (mm)	4311
Rim Rec	W 15 L
Rim Alt	W 14 L
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.40
30	2725

Printed on 4/20/2024 2:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..