

FARM 2000 - Teknik Özellikler



Description

FARM 2000 toprak işleme uygulamalarında kullanılan traktörler için uygun bir lastiktir. Daha fazla dayanıklılık sağlamak için kesilme ve kopmaya dirençli özel bir hamurla tasarlanmıştır. FARM 2000, güçlü gövdesi sayesinde yüksek yük kapasitesi sunar. Ayrıca, mükemmel çekiş ve kendi kendini temizleme özellikleri sağlar.

UM

US Standard

Construction



Machinery

Zirai: Traktör

Version	STANDARD
Туре	ТТ
Tyre Size	12.4 - 28
LI/SS	120 A8

Dimensions US Standard

Usa code	94002856
Ply Rating	8
Section Width (inch)	12.6
Overall Diameter (inch)	50.7
Static Loaded Radius (inch)	23.7
Rolling Circumference (inch)	156.3
Rim Rec	W 11
Rim Alt	W 9; W 10
TRA Code	R1

Load capacity (lbs)

mph / psi	34
25	3090

Printed on 4/9/2024 8:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..