

## FARM HIGHWAY TOUGH - Teknik Özellikler



### Description

FARM HIGHWAY TOUGH, römorklar ve uygulamalı makineler ile taşıma ve toprak işleme uygulamaları için tasarlanmış yüksek hızlı bir lastiktir. Yüksek hızlarda da yüksek yük kapasitesi sağlar ve uzun bir lastik kullanım ömrü sunar.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	9.5L - 15 FI

## Dimensions International Standard

<b>Ply Rating</b>	12
<b>Section Width (mm)</b>	245
<b>Overall Diameter (mm)</b>	766
<b>Static Loaded Radius (mm)</b>	343
<b>Rolling Circumference (mm)</b>	2183
<b>Rim Rec</b>	7.00
<b>Rim Alt</b>	8 LB

## Load capacity (Kg)

<b>km/h / bar</b>	<b>6.20</b>
<b>100</b>	<b>1550</b>

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/22/2025 2:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..