

FARM HIGHWAY TOUGH - Teknik Özellikler



Description

FARM HIGHWAY TOUGH, römorklar ve uygulamalı makineler ile taşıma ve toprak işleme uygulamaları için tasarlanmış yüksek hızlı bir lastiktir. Yüksek hızlarda da yüksek yük kapasitesi sağlar ve uzun bir lastik kullanım ömrü sunar.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	9.5L - 15 FI

Dimensions US Standard

Usa code	94039920
Ply Rating	8
Section Width (inch)	9.6
Overall Diameter (inch)	30.2
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	85.9
Rim Rec	7.00
Rim Alt	8 LB

Load capacity (lbs)

mph / psi	60
62	2680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/22/2025 12:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..