

FARM HIGHWAY TOUGH - Veri Sayfasını İndir



Description

FARM HIGHWAY TOUGH, römorklar ve uygulamalı makineler ile taşıma ve toprak işleme uygulamaları için tasarlanmış yüksek hızlı bir lastiktir. Yüksek hızlarda da yüksek yük kapasitesi sağlar ve uzun bir lastik kullanım ömrü sunar.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • Römork

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.00 - 15 FI	STANDARD	94044733	128 J	8	8 LB		10.8	33.6	0	0	TL	E11-54R-0017870
11L - 15 FI	STANDARD	94032518	128 J	12	8 LB	10 LB ; 8 J	11	30.6	13.7	87.2	TL	E11-54R-0017871
11L - 15 FI	STANDARD	94039937	120 J	8	8 LB	10 LB ; 8 J	11	30.6	13.7	87.2	TL	E11-54R-0018902
12.5L - 15 FI	STANDARD	94032525	134 J	12	10 LB		12.5	32.1	14.3	91.5	TL	E11-54R-0019049
9.5L - 15 FI	STANDARD	94037605		12	7.00	8 LB	9.6	30.2	13.5	85.9	TL	
9.5L - 15 FI	STANDARD	94039920		8	7.00	8 LB	9.6	30.2	13.5	85.9	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/22/2025 1:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..