

## FARM SPECIAL - Teknik Özellikler



### Description

FARM SPECIAL, toprak işleme operasyonları için uygun bir traktör lastiğidir. Güçlü gövde yüksek seviyede delinme direnci ve daha uzun kullanım ömrü sağlarken, yuvarlak omuzlar toprak hasarını önleyerek değeri ürünlerin korunmasını sağlar. FARM SPECIAL, üstün kendi kendini temizleme özellikleri için, özel çamur kırıcılar içeren benzersiz bir sırt tasarımına sahiptir. Ek olarak, çift açılı dişler mükemmel çekiş sağlar ve kaymayı azaltır.

### UM

US Standard

### Construction

 BIAS

### Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	13.6 - 36
LI/SS	125 A8

## Dimensions US Standard

Usa code	94061747
Ply Rating	8
Section Width (inch)	13.6
Overall Diameter (inch)	59.6
Static Loaded Radius (inch)	27.7
Rolling Circumference (inch)	180.7
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-005539
TRA Code	R1

## Load capacity (lbs)

mph / psi	30
25	3640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 1/15/2025 8:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..