

FL 639 - Teknik Özellikler



Description

FL 639, yarma uygulamaları için de uygun olan, araziye yönelik bir radyal yayılma lastiğidir. Geniş taban izi alanı, daha az toprak sıkışması sağlayarak ürün verimliliğinin artmasına neden olur. Güçlendirilmiş damak ve yanak koruması, lastik kullanım ömrünü uzatır. FL 639, mükemmel kendi kendini temizleme özelliklerinin yanı sıra olağanüstü çekiş sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Yayıcı

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	168 B/156 B
LI/SS DRIVE WHEEL	156 B
LI/SS FREE ROLLING	168 B

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1172
Static Loaded Radius (mm)	521
Rolling Circumference (mm)	3592
SRI (mm)	550
Rim Rec	AG 20.00
ECE	E11-106R-006478

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
50 FR	2180	2490	2800	3125	3450	3725	4000	4310	4625	4885	5150	5375	5600
50 DW	1550	1775	2000	2215	2430	2615	2800	3025	3250	3450	3650	3825	4000

Printed on 4/27/2024 10:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..