

## FL 639 - Teknik Özellikler



### Description

FL 639, yayma uygulamaları için de uygun olan, araziye yönelik bir radyal yayılma lastiğidir. Geniş taban izi alanı, daha az toprak sıkışması sağlayarak ürün verimliliğinin artmasına neden olur. Güçlendirilmiş damak ve yanak koruması, lastik kullanım ömrünü uzatır. FL 639, mükemmel kendi kendini temizleme özelliklerinin yanı sıra olağanüstü çekiş sağlar.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Yayıcı

Version	STANDARD
Type	TL
Tyre Size	710/40 R 22.5
LI/SS	170 B/158 B
LI/SS DRIVE WHEEL	158 B
LI/SS FREE ROLLING	170 B

## Dimensions International Standard

Section Width (mm)	727
Overall Diameter (mm)	1140
Static Loaded Radius (mm)	503
Rolling Circumference (mm)	3492
SRI (mm)	550
Rim Rec	AG 24.00
ECE	E11-106R-006479

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
50 FR	2300	2650	3000	3325	3650	3950	4250	4560	4875	5235	5600	5800	6000
50 DW	1650	1885	2120	2345	2575	2785	3000	3225	3450	3725	4000	4125	4250

Printed on 4/27/2024 5:45 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..