

## FLOTATION 351 - Teknik Özellikler



### Description

FLOTATION 351, römork kullanılan taşıma uygulamalarına en uygun çapraz katlı yayılma lastiğidir. Ekstra derin dişler üstün çekiş ve daha uzun lastik ömrü sağlar. FLOTATION 351, ıslak ve nemli yüzeylerde yüksek yük kapasitesi sağlayan ideal lastiktir.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: Römork

Version	STANDARD
Type	TL
Tyre Size	42 X 25.00 - 20
LI/SS	139 B

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	605
Overall Diameter (mm)	1110
Static Loaded Radius (mm)	508
Rolling Circumference (mm)	3302
Rim Rec	20.50 HF
Rim Alt	20.50 VF
ECE	E11-106R-004383
TRA Code	HF3

## Load capacity (Kg)

km/h / bar	3.70
50	2430

Printed on 4/9/2024 6:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..