

FLOTATION 351 - Teknik Özellikler



Description

FLOTATION 351, römork kullanılan taşıma uygulamalarına en uygun çapraz katlı yayılma lastiğidir. Ekstra derin dişler üstün çekiş ve daha uzun lastik ömrü sağlar. FLOTATION 351, ıslak ve nemli yüzeylerde yüksek yük kapasitesi sağlayan ideal lastiktir.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Römork

Version	STANDARD
Type	TL
Tyre Size	66 X 43.00 - 25
LI/SS	150 B

Dimensions US Standard

Usa code	94042999
Ply Rating	6
Section Width (inch)	40.2
Overall Diameter (inch)	68.9
Static Loaded Radius (inch)	30.8
Rolling Circumference (inch)	205.2
Rim Rec	36.0 TH
TRA Code	HF3

Load capacity (lbs)

mph / psi	15
30	7400

Printed on 4/26/2024 11:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..