

## FLOTATION 558 - Teknik Özellikler



### Description

FLOTATION 558, hem yolda hem de arazide saman biçerdöverleri/balya makineleri, tankerler ve römorklar için uygun bir çapraz katlı yayılma lastiğidir. İyi toprak işleme için yüksek yük kapasitesine ek olarak çekişin gerekli olduğu durumlarda özellikle tavsiye edilir.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Tanker • Römork

Version	ARAMID BELTED HD
Type	TL
Tyre Size	400/55 - 22.5
LI/SS DRIVE WHEEL	140 A8/136 B
LI/SS FREE ROLLING	152 A8/148 B

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	405
<b>Overall Diameter (mm)</b>	1020
<b>Static Loaded Radius (mm)</b>	445
<b>Rolling Circumference (mm)</b>	3084
<b>Rim Rec</b>	AG 11.75
<b>Rim Alt</b>	12.25 ; 13.00 ; AG 13.00
<b>ECE</b>	E11-106R-005350

## Load capacity (Kg)

km/h / bar	3.70	3.80	4.00
10 FR	4745	4825	4970
20 FR	4270	4340	4475
30 FR	3795	3860	3975
40 FR	3390	3445	3550
50 FR	3050	3100	3150
10 DW	3345	3395	3500
20 DW	3010	3055	3150
30 DW	2675	2715	2800
40 DW	2390	2425	2500
50 DW	2150	2185	2240

Printed on 4/25/2024 8:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..