

FLOTATION 558 - Teknik Özellikler



Description

FLOTATION 558, hem yolda hem de arazide saman biçerdöverleri/balya makineleri, tankerler ve römorklar için uygun bir çapraz katlı yayılma lastiğidir. İyi toprak işleme için yüksek yük kapasitesine ek olarak çekişin gerekli olduğu durumlarda özellikle tavsiye edilir.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Tanker • Römork

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 500/45 - 22.5 |
| LI/SS DRIVE WHEEL | 136 A8/132 B |
| LI/SS FREE ROLLING | 148 A8/144 B |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94006267 |
| Ply Rating | 12 |
| Section Width (inch) | 19.7 |
| Overall Diameter (inch) | 41.1 |
| Static Loaded Radius (inch) | 18.5 |
| Rolling Circumference (inch) | 124.7 |
| Rim Rec | AG 16.00 |
| ECE | E4-106R-002307 |

Load capacity (lbs)

| mph / psi | 33 | 36 | 39 |
|-----------|------|------|------|
| 5 FR | 8860 | 9290 | 9720 |
| 10 FR | 7970 | 8370 | 8750 |
| 20 FR | 7090 | 7430 | 7780 |
| 25 FR | 6330 | 6640 | 6940 |
| 30 FR | 5700 | 5970 | 6170 |
| 5 DW | 6290 | 6600 | 6910 |
| 10 DW | 5670 | 5940 | 6220 |
| 20 DW | 5040 | 5280 | 5530 |
| 25 DW | 4500 | 4720 | 4940 |
| 30 DW | 4050 | 4240 | 4410 |

Printed on 12/11/2023 8:17 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..