

FLOTATION 647 - Teknik Özellikler



Description

FLOTATION 647, yumuşak toprak ve çim sahalarda en iyi çekiş özelliğine sahip bir uygulama lastiğidir. Mükemmel kendi kendini temizleme özelliklerine ek olarak, özel olarak tasarlanmış sırt deseni, en uygun zemin basıncı ve yumuşak toprakta mükemmel performans sağlayan geniş bir temas alanı sağlar.

UM

International Standard

Construction

❖ BIAS

Machinery

Zirai: Uygulamalı makine

Version	STANDARD
Type	TL
Tyre Size	260/75 - 15.3
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	785
Static Loaded Radius (mm)	363
Rolling Circumference (mm)	2380
Rim Rec	9.00
ECE	E11-106R-005838

Load capacity (Kg)

km/h / bar	5.50
40 FR	1950
40 DW	1360

Printed on 4/26/2024 11:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..